

# O-Ring Standard Size (Metric)

MEASUREMENTS IN MILLIMETERS					MEASUREMENTS IN INCHES				
JIS B 2401 SIZE	ID	±	CS	±	JIS B 2401 SIZE	ID	±	CS	±
V10	9.50	0.17	4.00	0.10	V10	0.374	0.007	0.157	0.004
V15	14.50	0.20	4.00	0.10	V15	0.571	0.008	0.157	0.004
V24	23.50	0.24	4.00	0.10	V24	0.925	0.009	0.157	0.004
V34	33.50	0.33	4.00	0.10	V34	1.319	0.013	0.157	0.004
V40	39.50	0.37	4.00	0.10	V40	1.555	0.015	0.157	0.004
V55	54.50	0.49	4.00	0.10	V55	2.146	0.019	0.157	0.004
V58	57.50	0.52	4.00	0.10	V58	2.264	0.020	0.157	0.004
V70	69.00	0.61	4.00	0.10	V70	2.717	0.024	0.157	0.004
V85	84.00	0.72	4.00	0.10	V85	3.307	0.028	0.157	0.004
V100	99.00	0.83	4.00	0.10	V100	3.898	0.033	0.157	0.004
V120	119.00	0.97	4.00	0.10	V120	4.685	0.038	0.157	0.004
V140	138.50	1.08	4.00	0.10	V140	5.453	0.043	0.157	0.004
V150	148.50	1.18	4.00	0.10	V150	5.846	0.046	0.157	0.004
V175	173.00	1.36	4.00	0.10	V175	6.811	0.054	0.157	0.004
V225	222.50	1.70	6.00	0.15	V225	8.760	0.067	0.236	0.006
V275	272.00	2.02	6.00	0.15	V275	10.709	0.080	0.236	0.006
V315	312.00	2.22	6.00	0.15	V315	12.283	0.087	0.236	0.006
V325	321.50	2.34	6.00	0.15	V325	12.657	0.092	0.236	0.006
V380	376.00	2.68	6.00	0.15	V380	14.803	0.106	0.236	0.006
V430	425.50	2.99	6.00	0.15	V430	16.752	0.118	0.236	0.006
V475	470.50	3.22	6.00	0.15	V475	18.524	0.127	0.236	0.006
V480	475.00	3.30	10.00	0.30	V480	18.701	0.130	0.394	0.012
V490	485.00	3.31	10.00	0.30	V490	19.094	0.130	0.394	0.012
V510	504.50	3.44	10.00	0.30	V510	19.862	0.135	0.394	0.012
V530	524.50	3.60	10.00	0.30	V530	20.650	0.142	0.394	0.012
V585	579.00	3.92	10.00	0.30	V585	22.795	0.154	0.394	0.012
V640	633.50	4.24	10.00	0.30	V640	24.941	0.167	0.394	0.012
V690	683.00	4.54	10.00	0.30	V690	26.890	0.179	0.394	0.012
V740	732.50	4.83	10.00	0.30	V740	28.839	0.190	0.394	0.012
V790	782.00	5.12	10.00	0.30	V790	30.787	0.202	0.394	0.012
V950	940.50	6.06	10.00	0.30	V950	37.027	0.239	0.394	0.012
V1055	1044.0	6.67	10.00	0.30	V1055	41.102	0.263	0.394	0.012